

SAFETY DATA SHEET



FLORIDA PAINTS

5840 SPEED FREAK: Industrial Quik Dry Alkyd Gloss Enamel – WHITE

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name:	QUICK-DRY IND. GLOSS EN. – WHITE
Product Code:	5840
Product Use:	Enamel

Manufacturer

FLORIDA PAINTS
78 THIRD STREET
WINTER GARDEN, FL 34787 | 407.986.1000

24 Hour Emergency Telephone Number

CHEMTEL (US): (800)255-3924
CHEMTEL (International): (813)248-0585

2. HAZARDS IDENTIFICATION

Classification:	This material is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200) Aspiration Toxicity: Category 1 Carcinogenicity: Category 1A Germ Cell Mutagenicity: Category 1B Flammable Liquid: Category 2 Reproductive Toxicity: Category 1B
Signal Word:	Danger
Pictograms:	
Hazard Statements:	H225: Highly flammable liquid and vapor H304: May be fatal if swallowed and enters airways H340: May cause genetic defects H350: May cause cancer H360: May damage fertility or the unborn child
Prevention Precautionary Statements:	P201: Obtain special instructions before use P202: Do not handle until all safety precautions have been read and understood P210: Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. P233: Keep container tightly closed P240: Ground/bond container and receiving equipment P241: Use explosion-proof electrical/ventilating/lighting equipment P242: Use only non-sparking tools P243: Take precautionary measures against static discharge P281: Use personal protective equipment as required

Response Precautionary Statements:	P301+310: IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P308+313: IF exposed: Call a POISON CENTER or doctor/physician P370+378: In case of fire: Use CO ₂ , dry chemical, or foam to extinguish P331: Do NOT induce vomiting
Storage Precautionary Statements:	P405: Store locked up P403+235: Store in a well ventilated place. Keep cool.
Disposal Precautionary Statements:	P501: Dispose of contents/container to an approved waste disposal plant
Hazards Not Otherwise Classified:	None

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	Weight %	CAS Number
Xylenes (isomers and mixture)	20% to 30%	1330-20-7
Titanium dioxide	20% to 30%	13463-67-7
Ethylbenzene	10% to 20%	100-41-4
Solvent naptha, light aromatic	10% to 20%	67472-95-6
1,2,4-trimethylbenzene	1% to 5%	95-63-6
Silicon dioxide	1% to 5%	7631-86-9
Alumina trihydrate	1% to 5%	21645-51-2
Cumene	0% to 1%	98-82-8
Propylene glycol monomethyl ether	0% to 1%	107-98-2
Methyl ethyl ketoxime	0% to 1%	96-29-7
Zirconium dioxide	0% to 1%	1314-23-4
Aliphatic hydrocarbons	0% to 1%	64742-95-6

4. FIRST AID MEASURES

General Advice:	Call a physician if symptoms persist. Show SDS to physician.
Eyes:	Immediately flush with water. After initial flushing, remove contact lenses if applicable and continue flushing for at least 10 minutes. Keep eyes wide open while flushing. Consult a physician if symptoms persist.
Skin:	Remove contaminated clothing. Flush affected area with soap and water. Consult a physician if irritation persists. Wash contaminated clothing before re-use.
Ingestion:	Remove dentures if applicable and wash out mouth with water. Drink large amounts of water. Do not induce vomiting. Never give anything by mouth to an unconscious person. Consult a physician.
Inhalation:	Move to fresh air. If not breathing, give artificial respiration and consult a physician immediately. Consult a physician if symptoms persist.
Most Important Symptoms/Effects:	No information available
Notes to Physician:	Treat symptomatically

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media:	Foam, dry powder, CO ₂ , water spray. Use measures suitable to the circumstances and environment.
Precautions for Firefighters:	Wear self-contained breathing apparatus and protective gear
Specific Hazards:	Product is combustible. Thermal decomposition may release irritating gases/vapors. Explosive vapors may collect in low or confined areas.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions:	Remove all sources of ignition. Use proper personal protective equipment. Avoid contact with skin, eyes, and clothing. Avoid breathing vapors.
Other Precautions:	If safe to do so, prevent additional spillage. Do not allow material to enter ground water, surface water, or sewer system. Consult local authorities if spillage cannot be contained.
Clean-Up Method:	Soak up with non-combustible absorbent material. Dispose of used absorbent in suitable containers. Thoroughly clean contaminated surface.

7. HANDLING AND STORAGE

Handling Precautions:	Avoid contact with skin, eyes, and clothing. Avoid breathing vapors, mists, or dust. Use only in areas with sufficient ventilation. Ground all metal equipment to prevent ignition of vapors by static discharge. Keep away from heat and ignition sources.
Storage Precautions:	Keep container upright, properly labeled, tightly closed, and out of reach of children in a cool, dry, well-ventilated area. Keep away from heat and ignition sources.
Incompatible Materials:	Strong acids, strong bases, strong oxidizing agents

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

1,2,4-trimethylbenzene(95-63-6)		
ACGIH TWA:	25 ppm	--
NIOSH TWA:	25 ppm	125 mg/m ³
Cumene(98-82-8)		
ACGIH TWA:	50 ppm	--
NIOSH TWA:	50 ppm	245 mg/m ³
OSHA TWA:	50 ppm	245 mg/m ³
Ethylbenzene(100-41-4)		
ACGIH STEL:	125 ppm	--
ACGIH TWA:	20 ppm	--
NIOSH ST:	125 ppm	545 mg/m ³
NIOSH TWA:	100 ppm	435 mg/m ³
OSHA STEL:	125 ppm	545 mg/m ³
OSHA TWA:	100 ppm	435 mg/m ³
Methyl ethyl ketoxime(96-29-7)		
WEEL TWA:	10 ppm	--
Propylene glycol monomethyl ether(107-98-2)		
ACGIH STEL:	100 ppm	--
ACGIH TWA:	50 ppm	--
NIOSH ST:	150 ppm	540 mg/m ³

NIOSH TWA:	100 ppm	360 mg/m ³
Silicon dioxide(7631-86-9)		
NIOSH TWA:	6 mg/m ³	--
OSHA TWA:	20 mil particles/ft ³	80 mg/m ³ /%SiO ₂
Solvent naptha, light aromatic(67472-95-6)		
ACGIH:	100 ppm	--
OSHA:	100 ppm	--
Titanium dioxide(13463-67-7)		
TWA:	ACGIH: 10 mg/m ³	OSHA: 15 mg/m ³
Xylenes (isomers and mixture)(1330-20-7)		
ACGIH STEL:	150 ppm	--
ACGIH TWA:	100 ppm	--
OSHA TWA:	100 ppm	435 mg/m ³
Zirconium dioxide(1314-23-4)		
ACGIH:	TWA: 5 mg/m ³	STEL: 10 mg/m ³
NIOSH:	TWA: 5 mg/m ³	STEL: 10 mg/m ³
OSHA:	TWA: 5 mg/m ³	--

Engineering Measures:	Maintain adequate ventilation to keep exposure to airborne contaminants at safe levels. Use explosion-proof equipment.
Hygiene Measures:	No eating, drinking, or smoking while in use. Avoid contact with skin, eyes, and clothing. Wash hands, forearms, and face after handling. Wash contaminated clothing before re-use.
Eye/Face Protection:	Safety glasses/goggles
Skin Protection:	Protective gloves and long-sleeved protective clothing
Respiratory Protection:	NIOSH approved respirator if material is being used in a confined area, is being sprayed, or if exposure limits are exceeded

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Liquid
Color:	Determined by customer (white by default)
Odor:	Solvent
Odor Threshold:	No information available
pH:	No information available
Melting Point (°F):	No information available
Boiling Point (°F):	244.0 -246
Flash Point (°F):	59.00
Flash Point Method:	Closed cup
Evaporation Rate:	No information available
Flammability (Solid/Gas):	No information available
Flammability Limits:	No information available
Vapor Pressure (mm Hg):	No information available
Vapor Density:	No information available
Specific Gravity:	No information available
% Solubility in Water:	No information available
Octanol/Water Partition Coefficient:	No information available
Auto-Ignition Temperature (°F):	No information available

Decomposition Temperature (°F):	No information available
Viscosity (KU):	85-88
Volatile Organic Compounds (g/L):	534.4

10. STABILITY AND REACTIVITY

Reactivity:	No information available
Possibility of Hazardous Reactions:	None under normal conditions of use
Hazardous Decomposition Products:	Irritating vapors
Stability:	Stable under normal storage conditions
Incompatible Materials:	Strong acids, strong bases, strong oxidizing agents
Conditions to Avoid:	Heat, sparks, ignition sources

11. TOXICOLOGICAL INFORMATION

1,2,4-trimethylbenzene(95-63-6)	
Oral LD50 (rat):	6000 mg/kg
Aliphatic hydrocarbons(64742-95-6)	
Dermal LD50 (rabbit):	>2000 mg/kg
Inhalation LC50 (rat, 4 hrs):	10-20 ppm
Oral LD50 (rat):	>2000 mg/kg
Alumina trihydrate(21645-51-2)	
Oral LD50 (rat):	>2000 mg/kg
Cumene(98-82-8)	
NOAEL feed (rat):	>535.8 mg/kg
Oral LD50 (rat):	2260 mg/kg
Ethylbenzene(100-41-4)	
Dermal LD50 (rabbit):	15433 mg/kg
Oral LD50 (rat):	3500 mg/kg
Methyl ethyl ketoxime(96-29-7)	
Inhalation LC50 (rat, 4 hrs):	>4.83 mg/L
Oral LD50 (rat):	2326 mg/kg
Subcutaneous LD50 (rat):	2702 mg/kg
Propylene glycol monomethyl ether(107-98-2)	
Dermal LD50 (rabbit):	13000 mg/kg
Inhalation LC50 (rat, 5 hrs):	10000 ppm
Oral LD50 (mouse):	11700 mg/kg
Silicon dioxide(7631-86-9)	
Oral LD50 (rat):	3160 mg/kg
Solvent naphtha, light aromatic(67472-95-6)	
Dermal LD50:	>3160 mg/kg
Oral LD50:	>3000 mg/kg
Titanium dioxide(13463-67-7)	
Dermal LD50 (rabbit):	>10000 mg/kg
Oral LD50 (rat):	>10000 mg/kg

Primary Routes of Exposure:	Eye contact, skin contact, inhalation
------------------------------------	---------------------------------------

Acute Toxicity:	Repeated or prolonged exposure may to lead to permanent brain and nervous system damage. Inhalation of concentrated vapors may lead to death.
------------------------	---

Exposure Effects	
Eye Contact:	No information available
Skin Contact:	No information available
Inhalation:	No information available
Ingestion:	No information available
Target Organ (Single Exposure):	No information available
Target Organ (Repeated Exposure):	No information available
Sensitization:	No information available
Carcinogenicity:	No information available
Mutagenicity:	No information available
Reproductive Toxicity:	No information available
Other:	No information available

12. ECOLOGICAL INFORMATION

1,2,4-trimethylbenzene(95-63-6)	
Flow-through LC50 (fathead minnow, 96 hrs):	7.72 mg/L
Static EC50 (water flea, 48 hrs):	3.6 mg/L
Alumina trihydrate(21645-51-2)	
Semi-static NOEC (salmo trutta, 96 hrs):	>0.07 mg/L
Static NOEC (algae, 72 hrs):	>0.004 mg/L
Static NOEC (water flea, 48 hrs):	>0.005 mg/L
Cumene(98-82-8)	
EC50 (green algae, 72 hrs):	2.6 mg/L
EC50 (water flea, 48 hrs):	2.14 mg/L
LC50 (rainbow trout, 96 hrs):	4.8 mg/L
Ethylbenzene(100-41-4)	
Biodegradability (aerobic, 28 days):	70-80%
Flow-through LC50 (Atlantic silverside, 96 hrs):	5.1 mg/L
Static EC50 (Skeletonema costatum, 72 hrs):	4.9 mg/L
Static EC50 (water flea, 48 hrs):	1.8-2.4 mg/L
Methyl ethyl ketoxime(96-29-7)	
BCF (carp, 42 days, 2 mg/L):	0.5-0.6
Semi-static LC50 (Oryzias latipes, 96 hrs):	>100 mg/L
Static EC50 (freshwater algae, 72 hrs):	11.8 mg/L
Static EC50 (water flea, 48 hrs):	201 mg/L
Titanium dioxide(13463-67-7)	
EC50 (water flea, 48 hrs):	>1000 mg/L
LC50 (fish, 96 hrs):	>1000 mg/L
Zirconium dioxide(1314-23-4)	
LC50 (zebrafish, 96 hrs):	>100 mg/L
Static EC50 (water flea, 48 hrs):	>100 mg/L

Ecotoxicological Effects:	The environmental impact of this substance has not been fully evaluated
Persistence/Degradability:	No information available
Bioaccumulative Potential:	No information available

Environmental Mobility:	No information available
Other Effects:	No information available

13. DISPOSAL CONSIDERATIONS

Disposal Method:	Empty containers may contain flammable residue and vapors. Dispose of in accordance with federal, state, provincial, and local regulations.
-------------------------	---

14. TRANSPORT INFORMATION

DOT	
Shipping Name:	Paint
Hazard Class:	3
UN No:	1263
Packing Group:	II

ICAO/IATA	
Shipping Name:	Paint
Hazard Class:	3
UN No:	1263
Packing Group:	II

IMDG/IMO	
Shipping Name:	Paint
Hazard Class:	3
UN No:	1263
Packing Group:	II

15. REGULATORY INFORMATION

TSCA (US):	Not all components are listed
DSL/NDSL (Canada):	Not all components are listed

311/312 Hazard Categories	
Fire:	Yes
Pressure Generating:	No
Reactivity:	No
Acute:	Yes
Chronic:	Yes

CERCLA Section 302	
Reportable Quantities:	Ethylbenzene, 1000 lbs Xylenes (isomers and mixture), 100 lbs Cumene, 5000 lbs

SARA 313			
Chemical Name	CAS Number	Max Weight %	de minimis limit
Xylenes (isomers and mixture)	1330-20-7	30	1.0
Ethylbenzene	100-41-4	20	0.1
1,2,4-trimethylbenzene	95-63-6	5	1.0


State Right-to-Know						
Chemical Name	CAS Number	MA	NJ	PA	RI	
Xylenes (isomers and mixture)	1330-20-7	X	X	X	X	
Titanium dioxide	13463-67-7	X	X	X	X	
Ethylbenzene	100-41-4	X	X	X	X	
1,2,4-trimethylbenzene	95-63-6	X	X	X		
Silicon dioxide	7631-86-9	X	X	X		
Alumina trihydrate	21645-51-2		X	X		
Cumene	98-82-8	X	X	X	X	
Propylene glycol monomethyl ether	107-98-2	X	X	X	X	
Methyl ethyl ketoxime	96-29-7		X	X		
Zirconium dioxide	1314-23-4	X	X	X		
Aliphatic hydrocarbons	64742-95-6		X	X		

California Proposition 65:	This product contains small amounts of materials known to the state of California to cause cancer or reproductive harm. Titanium dioxide and silicon dioxide (airborne, unbound particles of respirable size) are known to the state of California to cause cancer. This listing does not cover titanium dioxide or silicon dioxide when they remain bound within a product matrix.
-----------------------------------	---

16. OTHER INFORMATION

HMIS RATING	
Health:	2*
Flammability:	3
Reactivity:	0
Personal Protection:	--

NFPA CODES



PPE rating has been left intentionally blank. Choose appropriate PPE based upon actual conditions of use.

Revision Indicator:	Revised 5/11/2018
Disclaimer:	The information contained in this Safety Data Sheet (SDS) is provided in good faith and is believed to be accurate as of the effective date listed. The information applies only to the product as provided and may not be valid if combined with other materials. No warranty is implied or given. The user is responsible for complying with all applicable laws and regulations.