

Liquid Release Concrete Stamp Release Agent

Release Agent • **6069**

Product Description

TropiCrete Liquid Release Concrete Stamp Solution is a colorless, bubblegum scented petroleum distillate formulated to release any decorative imprinting tool from concrete or polymer modified cementitious topping. It provides a lubricating barrier that protects and prolongs the life of stamping tools and evaporates from the cementitious surface leaving minimal residue.

Liquid Release Concrete Stamp Solution		Product Data	
Product Features		Product Type:	Petroleum Distillate
<ul style="list-style-type: none">Lubricating barrier to protect stamping toolsReduces occurrences of concrete sticking to stamping toolsPleasant bubblegum scent			
Companion Products		Wt Solids ±2%:	6069 N/A
<ul style="list-style-type: none">6061 TropiCrete DuraDek One 1-Part Stamp Overlay6062 TropiCrete DuraDek 2-Part Stamp Mix Concrete OverlayApproved stamp mix concrete overlay systems		Vol Solids ±2%:	N/A
Color: Translucent		VOC gms p/L:	0
Flash Point: 174°F Combustible			
Clean Up: Xylene or acetone		Product Limitations	
Coverage: Approximately 240 square feet per gallon		PROFESSIONAL USE ONLY - This product is designed for trained applicators. Limitations will apply the same as on bag mix products. Do not use in corrosive or chemical environments, or areas subject to intense heat.	
		Compliance	
		This product is VOC compliant with all Federal, State and Local VOC standards.	

Surface Preparation

Caution! There is the potential to release lead dust if you sand scrape or remove old paint. Lead is toxic and exposure to lead dust particles can cause serious illness including brain damage especially in children. Pregnant women should avoid exposure. If adequate ventilation is not possible, wear a NIOSH approved respirator to avoid inhalation of the fumes and wear clothing designed to prevent skin contact. Clean up carefully with a HEPA vacuum and a wet mop. Before starting your project, you can find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or visit their website at www.epa.gov/lead.

Directions for Use:

Specifically designed for use in conjunction with DuraDek Concrete Overlay systems: stamped concrete, stamped overlay, texture systems and imprinting or stamp tools. May be used on interior or exterior. Florida Paints recommends Liquid Release for projects that are to be textured, but colored later, e.g. stamp overlay and stamped concrete. Excessive masking associated with messy powder release is virtually eliminated with Liquid Release.

Application: Liquid Release is accomplished through misting the cementitious surface with a pump-up sprayer. Imprinting tools must have their texture face saturated at the start of stamping. Apply only as much release as can be covered with tools in a few minutes in temperatures above 40°F and rising. Direct sunlight and windy conditions will accelerate the evaporative properties of Liquid Release.

Thinning: Do not thin!

Clean-Up: Clean up all tools and equipment with xylene or acetone immediately after use.

Application Equipment: Use bag mix instructions.

Curing: Drying time and curing will affect the performance of the product. Do not apply when air, surface or product temperatures are below 40° F. or above 100° F. Surface temperature must be at least 5° F. above dew point. Plan ahead and avoid applying when damp or threatening weather is expected.

See bag mix instructions for additional information.

Safety - CAUTIONS: KEEP OUT OF REACH OF CHILDREN! DO NOT TAKE INTERNALLY! USE ONLY WITH ADEQUATE VENTILATION! Avoid prolonged contact with skin, and breathing of dust, vapors or spray mists. Avoid contact with eyes and wear eye protection. If adequate ventilation is not possible, wear a NIOSH approved respirator to avoid inhalation of the fumes and wear clothing designed to prevent skin contact. Wash skin thoroughly after handling. Close container after each use and store in a secure, shaded and dry location. **First Aid:** Wash skin thoroughly with plenty of warm soap and water. In case of eye contact immediately flush with plenty of water for 15 minutes and get medical attention immediately. If you experience difficulty breathing leave area to obtain fresh air. If continued difficulty is experienced get medical attention immediately. If swallowed do not induce vomiting and get medical attention immediately.

Storage and Disposal

Product should be kept from freezing temperatures or temperatures above 95°F. Refer to your local city or county government for instructions on disposal options.

Florida Paints believes the technical data represented in this technical bulletin to be current and up to date. However, Florida Paints makes no warranties or guarantees either expressed or implied. Florida Paints claims no responsibility from damages incurred from use by either the purchaser or user of the product.

PDS 6069 2007



Please excuse the small print used on this document but most paint company datasheets are two pages long. By squeezing all this information on one page we are doing our part to save a few trees.

Florida Paints and Coatings, LLC
78 3rd Street | Winter Garden, Florida 34787
407.986.1000 | info@FloridaPaints.com | FloridaPaints.com