

**Safety Data Sheet**  
acc. to OSHA HCS (29 CFR 1910.1200)



Printing date: 04/19/2018

Revision: 04/19/2018

### 1 Identification

- **Product identifier**
- **Trade name: Aquations Waterborne 2-Part Epoxy- Part A**
- **Product code: 5270**
- **Recommended use and restriction on use**
- **Recommended use:** Epoxy coating
- **Restrictions on use:** Contact manufacturer/supplier
- **Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**  
Florida Paints  
78 Third Street  
Winter Garden, FL 34787  
USA  
(407) 986-1000
- **Emergency telephone number:**  
ChemTel Inc.  
(800)255-3924, +1 (813)248-0585

### 2 Hazard(s) identification

- **Classification of the substance or mixture**  
Skin Irrit. 2 H315 Causes skin irritation.  
Eye Dam. 1 H318 Causes serious eye damage.  
STOT SE 1 H370 Causes damage to the stomach and the blood system. Route of exposure: Oral.  
STOT RE 1 H372 Causes damage to the kidneys through prolonged or repeated exposure. Route of exposure: Oral.
- **Label elements**
- **GHS label elements**  
The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms:**  
  
GHS05 GHS08
- **Signal word:** Danger
- **Hazard statements:**  
H315 Causes skin irritation.  
H318 Causes serious eye damage.  
H370 Causes damage to the stomach and the blood system. Route of exposure: Oral.  
H372 Causes damage to the kidneys through prolonged or repeated exposure. Route of exposure: Oral.
- **Precautionary statements:**  
P260 Do not breathe mist/vapors/spray.  
P264 Wash thoroughly after handling.  
P280 Wear protective gloves and eye protection.  
P270 Do not eat, drink or smoke when using this product.

(Cont'd. on page 2)



**Safety Data Sheet**  
acc. to OSHA HCS (29 CFR 1910.1200)

Printing date: 04/19/2018

Revision: 04/19/2018

**Trade name: 5270 WATERBORNE 2-PART EPOXY GLOSS - PART A**

(Cont'd. of page 1)

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P302+P352 IF ON SKIN: Wash with plenty of water.  
P332+P313 If skin irritation occurs: Get medical advice/attention.  
P314 Get medical advice/attention if you feel unwell.  
P362+P364 Take off contaminated clothing and wash it before reuse.  
P405 Store locked up.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Other hazards** There are no other hazards not otherwise classified that have been identified.

**3 Composition/information on ingredients**

· **Chemical characterization: Mixtures**

· **Components:**

	Trade Secret Aliphatic polyamine ⚠ STOT SE 1, H370; STOT RE 1, H372 ⚠ Eye Dam. 1, H318 ⚠ Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Irrit. 2, H315 Flam. Liq. 4, H227	20-40%
2807-30-9	2-(propyloxy)ethanol ⚠ Flam. Liq. 3, H226 ⚠ Acute Tox. 4, H312; Eye Irrit. 2A, H319	5-<10%
1344-28-1	aluminium oxide	1-2.5%
7631-86-9	silicon dioxide	0.1-1%
1314-23-4	zirconium dioxide	0.1-1%
57-55-6	propylene glycol	0.1-1%
126-86-3	2,4,7,9-tetramethyldec-5-yne-4,7-diol ⚠ Eye Dam. 1, H318 ⚠ Skin Sens. 1B, H317	0.1-<1%

· **Additional information:**

For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret.  
For the wording of the listed Hazard Statements refer to section 16.

**4 First-aid measures**

· **Description of first aid measures**

· **After inhalation:** Supply fresh air; consult doctor in case of complaints.

· **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

If skin irritation is experienced, consult a doctor.

· **After eye contact:**

Protect unharmed eye.

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. Then consult a doctor.

(Cont'd. on page 3)

# Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date: 04/19/2018

Revision: 04/19/2018

**Trade name: 5270 WATERBORNE 2-PART EPOXY GLOSS - PART A**

(Cont'd. of page 2)

- **After swallowing:**  
Rinse out mouth and then drink plenty of water.  
Do not induce vomiting; immediately call for medical help.
- **Most important symptoms and effects, both acute and delayed:**  
Irritant to skin and mucous membranes.  
Strong irritant with the danger of severe eye injury.  
Gastric or intestinal disorders when ingested.  
Nausea in case of ingestion.  
Diarrhea.
- **Danger:**  
Causes serious eye damage.  
Causes damage to the stomach and the blood system. Route of exposure: Oral.  
Causes damage to the kidneys through prolonged or repeated exposure. Route of exposure: Oral.  
May be harmful if swallowed.  
May be harmful if inhaled.
- **Indication of any immediate medical attention and special treatment needed:**  
Treat symptomatically.  
If medical advice is needed, have product container or label at hand.

## 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **For safety reasons unsuitable extinguishing agents:** None.
- **Special hazards arising from the substance or mixture**  
Formation of toxic gases is possible during heating or in case of fire.
- **Advice for firefighters**
- **Protective equipment:**  
Wear self-contained respiratory protective device.  
Wear fully protective suit.

## 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Ensure adequate ventilation.  
Use personal protective equipment as required.  
Particular danger of slipping on leaked/spilled product.
- **Environmental precautions**  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Methods and material for containment and cleaning up**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Do not allow to dry out  
Send for recovery or disposal in suitable receptacles.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.

(Cont'd. on page 4)



Printing date: 04/19/2018

Revision: 04/19/2018

**Trade name: 5270 WATERBORNE 2-PART EPOXY GLOSS - PART A**

See Section 13 for disposal information.

(Cont'd. of page 3)

**7 Handling and storage**

- **Handling**
- **Precautions for safe handling:**  
Open and handle receptacle with care.  
Use only in well ventilated areas.  
Keep out of reach of children.
- **Information about protection against explosions and fires:**  
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:**  
Store away from foodstuffs.  
Do not store together with acids.
- **Further information about storage conditions:** Keep containers tightly sealed.
- **Specific end use(s)** No relevant information available.

**8 Exposure controls/personal protection**

- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**

**2807-30-9 2-(propyloxy)ethanol**

EV (Canada)	Long-term value: 110 mg/m <sup>3</sup> , 25 ppm Skin
-------------	---

**1344-28-1 aluminium oxide**

PEL (USA)	Long-term value: 15* <sup>*</sup> ; 5** <sup>**</sup> mg/m <sup>3</sup> *Total dust; ** Respirable fraction
REL (USA)	Long-term value: 10* 5** mg/m <sup>3</sup> as Al*Total dust**Respirable/pyro powd./welding f.
TLV (USA)	Long-term value: 1* mg/m <sup>3</sup> as Al; *as respirable fraction
EL (Canada)	Long-term value: 1.0 mg/m <sup>3</sup> respirable, as Al
EV (Canada)	Long-term value: 10 mg/m <sup>3</sup> total dust
LMPE (Mexico)	Long-term value: 1* mg/m <sup>3</sup> A4, *fracciòn respirable

**7631-86-9 silicon dioxide**

NIOSH REL (USA)	Long-term value: 6 mg/m <sup>3</sup>
OSHA PEL (USA)	Long-term value: 80 mg/m <sup>3</sup>

(Cont'd. on page 5)



**Trade name: 5270 WATERBORNE 2-PART EPOXY GLOSS - PART A**

(Cont'd. of page 4)

**1314-23-4 zirconium dioxide**

PEL (USA)	Long-term value: 5 mg/m <sup>3</sup> as Zr
REL (USA)	Short-term value: 10 mg/m <sup>3</sup> Long-term value: 5 mg/m <sup>3</sup> as Zr
TLV (USA)	Short-term value: 10 mg/m <sup>3</sup> Long-term value: 5 mg/m <sup>3</sup> as Zr
EL (Canada)	Short-term value: 10 mg/m <sup>3</sup> Long-term value: 5 mg/m <sup>3</sup> as Zr
LMPE (Mexico)	Short-term value: 10 mg/m <sup>3</sup> Long-term value: 5 mg/m <sup>3</sup> A4; como Zr

**57-55-6 propylene glycol**

WEEL (USA)	Long-term value: 10 mg/m <sup>3</sup>
EV (Canada)	Long-term value: 155* 10** mg/m <sup>3</sup> , 50* ppm *vapour and aerosol;**aerosol only

**13463-67-7 titanium dioxide**

PEL (USA)	Long-term value: 15* mg/m <sup>3</sup> *total dust
REL (USA)	See Pocket Guide App. A
TLV (USA)	Long-term value: 10 mg/m <sup>3</sup> withdrawn from NIC
EL (Canada)	Long-term value: 10* 3** mg/m <sup>3</sup> *total dust;**respirable fraction; IARC 2B
EV (Canada)	Long-term value: 10 mg/m <sup>3</sup> total dust
LMPE (Mexico)	Long-term value: 10 mg/m <sup>3</sup> A4

• **Exposure controls**

• **Personal protective equipment:**

• **General protective and hygienic measures:**

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

• **Engineering controls:** Provide adequate ventilation.

• **Breathing equipment:**

Not required under normal conditions of use.

Wear appropriate NIOSH respirator when ventilation is inadequate and occupational exposure limits are exceeded.

(Cont'd. on page 6)

**Trade name: 5270 WATERBORNE 2-PART EPOXY GLOSS - PART A**

(Cont'd. of page 5)

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

- Neoprene gloves
- Nitrile rubber, NBR
- Butyl rubber, BR
- Natural rubber, NR
- Laminated film gloves.

· **Not suitable are gloves made of the following materials:**

- PVA gloves
- PVC gloves

· **Eye protection:**

Contact lenses should not be worn.



Safety glasses

· **Body protection:** Protective work clothing

· **Limitation and supervision of exposure into the environment**

Avoid release to the environment.

**9 Physical and chemical properties**

· **Information on basic physical and chemical properties**

· **Appearance:**

Form: Liquid

Color: White

· **Odor:** Mild

· **Odor threshold:** Not determined.

· **pH-value at 20 °C (68 °F):** 8.8

· **Melting point/Melting range:** Not determined.

· **Boiling point/Boiling range:** 260 °C (500 °F)

· **Flash point:** 253 °C (487 °F)

· **Flammability (solid, gaseous):** Not applicable.

· **Auto-ignition temperature:** Not determined.

· **Decomposition temperature:** Not determined.

· **Danger of explosion:** Product does not present an explosion hazard.

· **Explosion limits**

Lower: Not determined.

Upper: Not determined.

(Cont'd. on page 7)



Printing date: 04/19/2018

Revision: 04/19/2018

**Trade name: 5270 WATERBORNE 2-PART EPOXY GLOSS - PART A**

(Cont'd. of page 6)

· <b>Oxidizing properties:</b>	Not determined.
· <b>Vapor pressure at 20 °C (68 °F):</b>	27 hPa (20 mm Hg)
· <b>Density at 20 °C (68 °F):</b>	1.29 g/cm <sup>3</sup> (10.765 lbs/gal)
· <b>Relative density:</b>	Not determined.
· <b>Vapor density:</b>	Not determined.
· <b>Evaporation rate:</b>	Not determined.
· <b>Solubility in / Miscibility with Water:</b>	Fully miscible.
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity</b>	
<b>Dynamic at 20 °C (68 °F):</b>	3500 cPs
<b>Kinematic:</b>	Not determined.
<b>VOC content:</b>	276 g/L (Less water)
· <b>Other information</b>	No relevant information available.

### 10 Stability and reactivity

- **Reactivity:** No relevant information available.
- **Chemical stability:** Stable under normal temperatures and pressures.
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions**  
Reacts with oxidizing agents.  
Reacts with acids.
- **Conditions to avoid**  
Avoid acids.  
Excessive heat.
- **Incompatible materials**  
Oxidizing agents  
Strong acids
- **Hazardous decomposition products**  
Carbon monoxide and carbon dioxide  
Nitrogen oxides (NOx)

### 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **LD/LC50 values that are relevant for classification:**

**2807-30-9 2-(propyloxy)ethanol**

Oral	LD50	1800 mg/kg (mouse)
------	------	--------------------

(Cont'd. on page 8)



Printing date: 04/19/2018

Revision: 04/19/2018

**Trade name: 5270 WATERBORNE 2-PART EPOXY GLOSS - PART A**

(Cont'd. of page 7)

Dermal	LD50	3100 mg/kg (rat) 1300 mg/kg (rabbit)
--------	------	---

- **Primary irritant effect:**
- **On the skin:** Irritant to skin and mucous membranes.
- **On the eye:** Strong irritant with the danger of severe eye injury.
- **Sensitization:**  
Based on available data, the classification criteria are not met.  
Contains 2,4,7,9-tetramethyldec-5-yne-4,7-diol. May produce an allergic reaction.

• **Carcinogenic categories**

• **IARC (International Agency for Research on Cancer):**

13463-67-7	titanium dioxide	2B
7631-86-9	silicon dioxide	3

• **NTP (National Toxicology Program):**

None of the ingredients are listed.

• **OSHA-Ca (Occupational Safety & Health Administration):**

None of the ingredients are listed.

• **Probable route(s) of exposure:**

- Ingestion.
- Inhalation.
- Eye contact.
- Skin contact.

- **Acute effects (acute toxicity, irritation and corrosivity):** Causes serious eye damage.
- **Repeated dose toxicity:** Danger of very serious irreversible effects.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity:** Based on available data, the classification criteria are not met.
- **Carcinogenicity:** Based on available data, the classification criteria are not met.
- **Reproductive toxicity:** Based on available data, the classification criteria are not met.
- **STOT-single exposure:** Causes damage to the stomach and the blood system. Route of exposure: Oral.
- **STOT-repeated exposure:**  
Causes damage to the kidneys through prolonged or repeated exposure. Route of exposure: Oral.
- **Aspiration hazard:** Based on available data, the classification criteria are not met.

**12 Ecological information**

- **Toxicity**
- **Aquatic toxicity** No relevant information available.
- **Persistence and degradability** No relevant information available.
- **Bioaccumulative potential:** No relevant information available.
- **Mobility in soil:** No relevant information available.
- **Additional ecological information**
- **General notes:**  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

(Cont'd. on page 9)





Printing date: 04/19/2018

Revision: 04/19/2018

**Trade name: 5270 WATERBORNE 2-PART EPOXY GLOSS - PART A**

· **Other adverse effects** No relevant information available.

(Cont'd. of page 8)

### 13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

Can be disposed of with household garbage after solidification following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations. The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

· **Uncleaned packagings**

· **Recommendation:** Disposal must be made according to official regulations.

### 14 Transport information

· **UN-Number**

· DOT, ADR, IMDG, IATA Not regulated.

· **UN proper shipping name**

· DOT, ADR, IMDG, IATA Not regulated.

· **Transport hazard class(es)**

· DOT, ADR, IMDG, IATA

· Class Not regulated.

· **Packing group**

· DOT, ADR, IMDG, IATA Not regulated.

· **Environmental hazards**

Not applicable.

· **Special precautions for user**

Not applicable.

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

### 15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **United States (USA)**

· **SARA**

· **Section 302 (extremely hazardous substances):**

None of the ingredients are listed.

(Cont'd. on page 10)



Printing date: 04/19/2018

Revision: 04/19/2018

**Trade name: 5270 WATERBORNE 2-PART EPOXY GLOSS - PART A**

(Cont'd. of page 9)

**Section 304 (emergency release notification):**

None of the ingredients are listed.

**Section 355 (extremely hazardous substances):**

None of the ingredients are listed.

**Section 313 (Specific toxic chemical listings):**

1344-28-1 aluminium oxide

**TSCA (Toxic Substances Control Act)**

All ingredients are listed.

**Proposition 65 (California)**

**Chemicals known to cause cancer:**

Reference to titanium dioxide is based on unbound respirable particles and is not generally applicable to product as supplied.

13463-67-7 titanium dioxide

**Chemicals known to cause reproductive toxicity for females:**

None of the ingredients are listed.

**Chemicals known to cause reproductive toxicity for males:**

None of the ingredients are listed.

**Chemicals known to cause developmental toxicity:**

None of the ingredients are listed.

**Carcinogenic categories**

**EPA (Environmental Protection Agency):**

None of the ingredients are listed.

**IARC (International Agency for Research on Cancer):**

Reference to chemical component(s) listed below are based on unbound respirable particles and are not generally applicable to product as supplied.

13463-67-7 titanium dioxide

2B

7631-86-9 silicon dioxide

3

**NIOSH-Ca (National Institute for Occupational Safety and Health):**

13463-67-7 titanium dioxide

**16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**Date of preparation / last revision** 12/15/2016 / -

**Abbreviations and acronyms:**

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NIOSH: National Institute for Occupational Safety

(Cont'd. on page 11)



**Safety Data Sheet**  
acc. to OSHA HCS (29 CFR 1910.1200)

Printing date: 04/19/2018

Revision: 04/19/2018

**Trade name: 5270 WATERBORNE 2-PART EPOXY GLOSS - PART A**

(Cont'd. of page 10)

OSHA: Occupational Safety & Health  
TLV: Threshold Limit Value  
PEL: Permissible Exposure Limit  
REL: Recommended Exposure Limit  
LDLo: Lowest Lethal Dose Observed  
Flam. Liq. 3: Flammable liquids – Category 3  
Flam. Liq. 4: Flammable liquids – Category 4  
Acute Tox. 4: Acute toxicity – Category 4  
Skin Irrit. 2: Skin corrosion/irritation – Category 2  
Eye Dam. 1: Serious eye damage/eye irritation – Category 1  
Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A  
Skin Sens. 1B: Skin sensitisation – Category 1B  
STOT SE 1: Specific target organ toxicity (single exposure) – Category 1  
STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

• **Sources**

Website, European Chemicals Agency ([echa.europa.eu](http://echa.europa.eu))  
Website, US EPA Substance Registry Services ([ofmpub.epa.gov/sorinternet/registry/substreg/home/overview/home.do](http://ofmpub.epa.gov/sorinternet/registry/substreg/home/overview/home.do))  
Website, Chemical Abstracts Registry, American Chemical Society ([www.cas.org](http://www.cas.org))  
Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6  
Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaassen, Curtis D., ed., ISBN: 978-0-07-176923-5.  
Safety Data Sheets, Individual Manufacturers

SDS Prepared by:  
ChemTel Inc.  
1305 North Florida Avenue  
Tampa, Florida USA 33602-2902  
Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573  
Website: [www.chemtelinc.com](http://www.chemtelinc.com)

**Safety Data Sheet**  
acc. to OSHA HCS (29 CFR 1910.1200)

Printing date: 04/19/2018

Revision: 04/19/2018

**1 Identification**

- **Product identifier**
- **Trade name: Aquations 2-Part Epoxy Gloss - Part B**
- **Product code: 5279**
- **Recommended use and restriction on use**
- **Recommended use:** Epoxy coating
- **Restrictions on use:** Contact manufacturer/supplier
- **Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**  
Florida Paints  
78 Third Street  
Winter Garden, FL 34787  
USA  
407-986-1000
- **Emergency telephone number:**  
ChemTel Inc.  
(800)255-3924, +1 (813)248-0585

**2 Hazard(s) identification**

- **Classification of the substance or mixture**  
Skin Irrit. 2 H315 Causes skin irritation.  
Eye Irrit. 2A H319 Causes serious eye irritation.  
Skin Sens. 1 H317 May cause an allergic skin reaction.

-----  
· **Label elements**

- **GHS label elements**  
The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms:**



GHS07

- **Signal word:** Warning
- **Hazard statements:**  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H317 May cause an allergic skin reaction.
- **Precautionary statements:**  
P261 Avoid breathing mist, vapors, or spray.  
P264 Wash thoroughly after handling.  
P280 Wear protective gloves and eye protection.  
P272 Contaminated work clothing must not be allowed out of the workplace.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P302+P352 IF ON SKIN: Wash with plenty of water.  
P363 Wash contaminated clothing before reuse.

(Cont'd. on page 2)

# Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date: 04/19/2018

Revision: 04/19/2018

**Trade name: 5279 WATERBORNE 2-PART EPOXY GLOSS - PART B**

(Cont'd. of page 1)







P333+P313 If skin irritation or rash occurs: Get medical advice/attention.  
 P337+P313 If eye irritation persists: Get medical advice/attention.  
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Other hazards** There are no other hazards not otherwise classified that have been identified.

### 3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Components:**

25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight $\leq$ 700)  Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317	60-80%
763-69-0	Ethyl 3-ethoxypropionate  Flam. Liq. 3, H226  Asp. Tox. 1, H304  Eye Irrit. 2A, H319	20-40%
577-11-7	sodium dioctyl sulfosuccinate  Eye Dam. 1, H318  Skin Irrit. 2, H315	1-2.5%
57-55-6	propylene glycol	0.1-1%

· **Additional information:**

For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret.  
 For the wording of the listed Hazard Statements refer to section 16.

### 4 First-aid measures

· **Description of first aid measures**

· **After inhalation:** Supply fresh air; consult doctor in case of complaints.

· **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

If skin irritation or rash occurs: Get medical advice/attention.

· **After eye contact:**

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. Then consult a doctor.

· **After swallowing:**

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; immediately call for medical help.

· **Most important symptoms and effects, both acute and delayed:**

Headache

Coughing

Irritant to skin and mucous membranes.

Irritant to eyes.

Allergic reactions

Gastric or intestinal disorders when ingested.

Nausea in case of ingestion.

(Cont'd. on page 3)



**Safety Data Sheet**  
acc. to OSHA HCS (29 CFR 1910.1200)

Printing date: 04/19/2018

Revision: 04/19/2018

**Trade name: 5279 WATERBORNE 2-PART EPOXY GLOSS - PART B**

(Cont'd. of page 2)

Vomiting.

Diarrhea.

• **Danger:**

May be harmful if swallowed.

May be harmful if inhaled.

• **Indication of any immediate medical attention and special treatment needed:**

Medical supervision for at least 48 hours.

Later observation for pneumonia and pulmonary edema.

If necessary oxygen respiration treatment.

Treat skin and mucous membrane with antihistamine and corticoid preparations.

Contains reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight  $\leq$  700). May produce an allergic reaction.

If medical advice is needed, have product container or label at hand.

## 5 Fire-fighting measures

• **Extinguishing media**

• **Suitable extinguishing agents:**

Water fog / haze

Foam

Carbon dioxide

Gaseous extinguishing agents

BC powder

Fire-extinguishing powder

• **For safety reasons unsuitable extinguishing agents:** Water stream.

• **Special hazards arising from the substance or mixture**

Formation of toxic gases is possible during heating or in case of fire.

• **Advice for firefighters**

• **Protective equipment:**

Wear self-contained respiratory protective device.

Wear fully protective suit.

## 6 Accidental release measures

• **Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation.

Use personal protective equipment as required.

Particular danger of slipping on leaked/spilled product.

Protect from heat

• **Environmental precautions**

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

• **Methods and material for containment and cleaning up**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Do not allow to dry out

Send for recovery or disposal in suitable receptacles.

(Cont'd. on page 4)



**Safety Data Sheet**  
acc. to OSHA HCS (29 CFR 1910.1200)

Printing date: 04/19/2018

Revision: 04/19/2018

**Trade name: 5279 WATERBORNE 2-PART EPOXY GLOSS - PART B**

(Cont'd. of page 3)

· **Reference to other sections**

- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

**7 Handling and storage**

· **Handling**

· **Precautions for safe handling:**

- Open and handle receptacle with care.
- Use only in well ventilated areas.
- Keep out of reach of children.

· **Information about protection against explosions and fires:**

- Keep ignition sources away - Do not smoke.
- Protect from heat.
- Keep respiratory protective device available.

· **Conditions for safe storage, including any incompatibilities**

· **Storage**

· **Requirements to be met by storerooms and receptacles:** Store in a well-ventilated place. Keep cool.

· **Information about storage in one common storage facility:**

- Store away from foodstuffs.
- Store away from oxidizing agents.
- Do not store together with acids.

· **Further information about storage conditions:** Keep containers tightly sealed.

· **Specific end use(s)** No relevant information available.

**8 Exposure controls/personal protection**

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

**763-69-0 Ethyl 3-ethoxypropionate**

STEL (USA)	Ceiling limit value: 600 mg/m <sup>3</sup> 100 ppm converted to mg/m <sup>3</sup>
TWA (USA)	Ceiling limit value: 300 mg/m <sup>3</sup> Converted from 50 ppm
TWA (Canada)	Short-term value: 300 mg/m <sup>3</sup>

**57-55-6 propylene glycol**

WEEL (USA)	Long-term value: 10 mg/m <sup>3</sup>
EV (Canada)	Long-term value: 155* 10** mg/m <sup>3</sup> , 50* ppm *vapour and aerosol;**aerosol only

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

The usual precautionary measures for handling chemicals should be followed.

(Cont'd. on page 5)

**Safety Data Sheet**  
acc. to OSHA HCS (29 CFR 1910.1200)

Printing date: 04/19/2018

Revision: 04/19/2018

**Trade name: 5279 WATERBORNE 2-PART EPOXY GLOSS - PART B**

(Cont'd. of page 4)

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- **Engineering controls:** Provide adequate ventilation.

- **Breathing equipment:**

Not required under normal conditions of use.

Wear appropriate NIOSH respirator when ventilation is inadequate and occupational exposure limits are exceeded.

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- **Material of gloves**

Neoprene gloves

Nitrile rubber, NBR

Butyl rubber, BR

Natural rubber, NR

Laminated film gloves.

- **Not suitable are gloves made of the following materials:**

PVA gloves

PVC gloves

- **Eye protection:**



Safety glasses

- **Body protection:** Protective work clothing

- **Limitation and supervision of exposure into the environment**

Avoid release to the environment.

## 9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **Appearance:**

**Form:** Liquid

**Color:** White

- **Odor:** Mild

- **Odor threshold:** Not determined.

- **pH-value at 20 °C (68 °F):** 8.8

- **Melting point/Melting range:** Not determined.

- **Boiling point/Boiling range:** 260 °C (500 °F)

- **Flash point:** 253 °C (487 °F)

- **Flammability (solid, gaseous):** Not applicable.

(Cont'd. on page 6)



# Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date: 04/19/2018

Revision: 04/19/2018

**Trade name: 5279 WATERBORNE 2-PART EPOXY GLOSS - PART B**

(Cont'd. of page 5)

· <b>Auto-ignition temperature:</b>	Not determined.
· <b>Decomposition temperature:</b>	Not determined.
· <b>Danger of explosion:</b>	Product does not present an explosion hazard.
· <b>Explosion limits</b> <b>Lower:</b>	Not determined.
<b>Upper:</b>	Not determined.
· <b>Oxidizing properties:</b>	Not determined.
· <b>Vapor pressure:</b>	Not determined.
· <b>Density at 20 °C (68 °F):</b>	1.09 g/cm <sup>3</sup> (9.096 lbs/gal)
· <b>Relative density:</b>	Not determined.
· <b>Vapor density:</b>	Not determined.
· <b>Evaporation rate:</b>	Not determined.
· <b>Solubility in / Miscibility with</b> <b>Water:</b>	Partly miscible.
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity</b> <b>Dynamic:</b>	1000 cPs
<b>Kinematic:</b>	Not determined.
<b>VOC content:</b>	276 g/L (Less water)
· <b>Other information</b>	No relevant information available.

## 10 Stability and reactivity

- **Reactivity:** No relevant information available.
- **Chemical stability:** Stable under normal temperatures and pressures.
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions**  
Reacts with oxidizing agents.  
Reacts with acids.  
Reacts with peroxides and other radical forming substances.
- **Conditions to avoid**  
Avoid acids.  
Excessive heat.  
Keep away from oxidizing agents.
- **Incompatible materials**  
Oxidizing agents  
Strong acids
- **Hazardous decomposition products**  
Possible in traces:  
Carbon monoxide and carbon dioxide  
Nitrogen oxides (NO<sub>x</sub>)

(Cont'd. on page 7)

Printing date: 04/19/2018

Revision: 04/19/2018

**Trade name: 5279 WATERBORNE 2-PART EPOXY GLOSS - PART B**

Sulfur oxides (SOx)  
Hydrogen chloride (HCl)  
Chlorine compounds

(Cont'd. of page 6)

### 11 Toxicological information

· **Information on toxicological effects**

· **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

**25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ½ 700)**

Oral	LD50	>2000 mg/kg (rat, female)
------	------	---------------------------

Dermal	LD50	>2000 mg/kg (rat)
--------	------	-------------------

**577-11-7 sodium dioctyl sulfosuccinate**

Oral	LD50	> 3000 mg/kg (rat)
------	------	--------------------

· **Primary irritant effect:**

- **On the skin:** Irritant to skin and mucous membranes.
- **On the eye:** Irritating effect.
- **Sensitization:** Sensitization possible through skin contact.

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer):**

None of the ingredients are listed.

· **NTP (National Toxicology Program):**

None of the ingredients are listed.

· **OSHA-Ca (Occupational Safety & Health Administration):**

None of the ingredients are listed.

· **Probable route(s) of exposure:**

- Ingestion.
- Inhalation.
- Eye contact.
- Skin contact.

· **Repeated dose toxicity:** Danger of very serious irreversible effects.

· **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**

- **Germ cell mutagenicity:** Based on available data, the classification criteria are not met.
- **Carcinogenicity:** Based on available data, the classification criteria are not met.
- **Reproductive toxicity:** Based on available data, the classification criteria are not met.
- **STOT-single exposure:** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure:** Based on available data, the classification criteria are not met.
- **Aspiration hazard:** Based on available data, the classification criteria are not met.

(Cont'd. on page 8)

**Safety Data Sheet**  
acc. to OSHA HCS (29 CFR 1910.1200)

Printing date: 04/19/2018

Revision: 04/19/2018

**Trade name: 5279 WATERBORNE 2-PART EPOXY GLOSS - PART B**

(Cont'd. of page 7)

**12 Ecological information**

- **Toxicity**
- **Aquatic toxicity**  
Toxic to aquatic life with long lasting effects.

**25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ½ 700)**

EC50	2.7 mg/kg (daphnia) (48hr)
LC50	1.2 mg/l (Oncorhynchus mykiss) (96hr)
	2.4 mg/l (zebra fish) (96hr)

**763-69-0 Ethyl 3-ethoxypropionate**

LC50	62 mg/l (pimephales promelas)
EC50	970 mg/l (daphnia)

- **Persistence and degradability** No relevant information available.
- **Bioaccumulative potential:** No relevant information available.
- **Mobility in soil:** No relevant information available.
- **Ecotoxicological effects:**
- **Remark:**  
Toxic for fish  
Toxic for water fleas
- **Additional ecological information**
- **General notes:** Do not allow product to reach ground water, water course or sewage system.
- **Other adverse effects** No relevant information available.

**13 Disposal considerations**

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system. Can be disposed of with household garbage after solidification following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations. The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.
- **Uncleaned packagings**
- **Recommendation:** Disposal must be made according to official regulations.

**14 Transport information**

- **UN-Number**
- **DOT** Not regulated.
- **ADR, IMDG, IATA** UN3082

(Cont'd. on page 9)

**Safety Data Sheet**  
acc. to OSHA HCS (29 CFR 1910.1200)

Printing date: 04/19/2018

Revision: 04/19/2018

**Trade name: 5279 WATERBORNE 2-PART EPOXY GLOSS - PART B**

(Cont'd. of page 8)

· **UN proper shipping name**  
· DOT  
· ADR, IMDG  
· IATA

Not regulated.  
ENVIRONMENTALLY HAZARDOUS SUBSTANCE,  
LIQUID, N.O.S. (BISPHENOL A EPOXY RESIN)  
Environmentally hazardous substance, liquid, n.o.s.  
(Bisphenol A epoxy resin)

· **Transport hazard class(es)**  
· DOT  
· Class

Not regulated.


· ADR



· Class  
· Label

9 (M6) Miscellaneous dangerous substances and articles  
9

· IMDG, IATA



· Class  
· Label

9 Miscellaneous dangerous substances and articles  
9

· **Packing group**  
· DOT  
· ADR, IMDG, IATA

Not regulated.  
III

· **Environmental hazards**  
· **Marine pollutant:**

Product contains environmentally hazardous substances: reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight  $\leq 700$ )  
Symbol (fish and tree)

· **Special precautions for user**  
· **Danger code (Kemler):**  
· **EMS Number:**

Warning: Miscellaneous dangerous substances and articles  
90  
F-A,S-F

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

· **Transport/Additional information:**

Not regulated when carried in single or combination packaging containing a net quantity of 5L or less for liquids or 5 kg or less for solids per the following:  
DOT: 171.4(c)(2)  
ADR: SP 375  
IMDG: 2.10.2.7

(Cont'd. on page 10)

Printing date: 04/19/2018

Revision: 04/19/2018

**Trade name: 5279 WATERBORNE 2-PART EPOXY GLOSS - PART B**

(Cont'd. of page 9)

- IATA: special provision A197
- DOT Product is additionally classified as a MARINE POLLUTANT based on MARPOL and DOT rules. Labeling as a MARINE POLLUTANT is not required for non-bulk single package shipments by motor vehicle, rail car or aircraft. Bulk packaging consists of a maximum capacity of greater than 450L (119 gallons) for a liquid and a maximum net mass greater than 400kg (882 pounds) for a solid.

**15 Regulatory information**

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **United States (USA)**
- **SARA**

· **Section 302 (extremely hazardous substances):**

None of the ingredients are listed.

· **Section 304 (emergency release notification):**

None of the ingredients are listed.

· **Section 355 (extremely hazardous substances):**

None of the ingredients are listed.

· **Section 313 (Specific toxic chemical listings):**

None of the ingredients are listed.

· **TSCA (Toxic Substances Control Act)**

Some ingredients listed.

· **Proposition 65 (California)**

· **Chemicals known to cause cancer:**

None of the ingredients are listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients are listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients are listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients are listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency):**

None of the ingredients are listed.

· **IARC (International Agency for Research on Cancer):**

None of the ingredients are listed.

(Cont'd. on page 11)



**Safety Data Sheet**  
acc. to OSHA HCS (29 CFR 1910.1200)

Printing date: 04/19/2018

Revision: 04/19/2018

**Trade name: 5279 WATERBORNE 2-PART EPOXY GLOSS - PART B**

(Cont'd. of page 10)

· **NIOSH-Ca (National Institute for Occupational Safety and Health):**

None of the ingredients are listed.

**16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Date of preparation / last revision** 12/15/2016 / -

· **Abbreviations and acronyms:**

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

LDLo: Lowest Lethal Dose Observed

Flam. Liq. 3: Flammable liquids – Category 3

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Skin Sens. 1: Skin sensitisation – Category 1

Asp. Tox. 1: Aspiration hazard – Category 1

· **Sources**

Website, European Chemicals Agency ([echa.europa.eu](http://echa.europa.eu))

Website, US EPA Substance Registry Services ([ofmpub.epa.gov/sor-internet/registry/substreg/home/overview/home.do](http://ofmpub.epa.gov/sor-internet/registry/substreg/home/overview/home.do))

Website, Chemical Abstracts Registry, American Chemical Society ([www.cas.org](http://www.cas.org))

Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6

Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5.

Safety Data Sheets, Individual Manufacturers

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: [www.chemtelinc.com](http://www.chemtelinc.com)